

INSTALL INSTRUCTIONS C-VS-1100-F150 VEHICLE SPECIFIC CONSOLE 2004-2008 FORD F-150 PICK UP

TOOLS REQUIRED:

Metric Socket Set
Ratcheting Wrench
Panel Pulling Tool

1/8" Drill Bit
Phillips Screwdriver
Power Drill

HARDWARE:

QTY DESCRIPTION

6 #8 x 3/4" Phillip Sheet Metal Screws
1 C-HK-1 (32 Torx Screws)

PART

GSM33189
CM86508

SUB ASSEMBLY:

1. Remove necessary components to access mounting area.
 - Armrest Pad (3 Metric Hex Head screws)
 - Forward Console Face Plate (Panel Pulling Tool)
 - Rear Console Face Plate (Panel Pulling Tool & 2 Metric Hex Head Screws)



INSTALLATION:

1. ATTACH HAVIS, INC. CONSOLE:

- Position console plate as shown in the above view.
- Pre-drill mounting holes with 1/8" drill bit.
- Attach console plate using #8 x 3/4" Sheet Metal Screws.

2. REPLACE COMPONENTS REMOVED IN SUB ASSEMBLY:

- Replace Rear Console Face Plate.
- Replace Forward Console Face Plate.
- Replace Armrest Pad.

3. INSTALL CONTROLS:

- Wire all controls prior to installation.

Note: A hole must be drilled in the bottom of the OEM console for routing of wires.

- Attach control heads to console plate using equipment brackets or filler panels with #8 x 3/8" Black Torx Screws.

Note: You may have to drill the console plate in the occasional situation that the mounting slots do not line up with the equipment bracket.

