Havis Docking Station
Fully Rugged Z710 & ZX70
DS-GTC-700

Getac

Rugged Tablet Solution

- Low profile, lightweight and flexible design
- Port replication with integrated strain relieving
- Dual Pass-Thru Antenna Connections (Optional)
- External Power Supply (Optional)
- Bundles available for convenient solutions

PART NUMBER	ETHERNET	USB 2.0	USB 3.0	HDMI	VGA	SERIAL	POWERED SERIAL	DISPLAY PORT	SPEAKER/ MIC	POWER INPUT	PASS-THRU ANT	ANT TYPE	EXT POWER	INT POWER
DS-GTC-701**	1	2 Rear		1		1			Speaker	12 V*				
DS-GTC-701-2**	1	2 Rear		1		1			Speaker	12 V*	Dual	SMA		
DS-GTC-703														
DS-GTC-703-2											Dual	SMA		
DS-GTC-704***	1	2 Rear		1		1			Speaker	12 V*				
DS-GTC-704-2***	1	2 Rear		1		1			Speaker	12 V*	Dual	SMA		
DS-GTC-705***										12 V*				
DS-GTC-705-2***										12 V*	Dual	SMA		
DS-GTC-706													LPS-139	
DS-GTC-706-2											Dual	SMA	LPS-139	

** Requires an external Getac authorized DC power supply*
*** JAE Docking Connector*
**** POGO Docking Connector*

SPECIFICATIONS

Height: 8.7-in (22.1 cm)
Width: 9.2-in (23.4 cm)
Depth: 2.9-in (7.4 cm)
Weight: 1.5 lbs (0.7 kg)
Mounting: VESA 75

CERTIFICATIONS & TESTING

CE Certified; RoHS Compliant
Vibration Testing: MIL-STD 810G 514.5
Impact Test: Crash Simulation per SAE J1455
Cycle Test: Latch Tested 30,000 cycles
Environmental Testing: Hot/Cold Operation & Storage